

Certified PDF

Diecut • Line of 0.5 pt in Pantone 3405CV and on **overprint**.
• A **standard** bore (hole) is Ø 5 mm and 5 mm from the cutting edge.
If it's not standard ask for more specifications concerning the accessories related to the labels.

Layout • Text and/or images at least 2 mm from the cutting edge.
• Line thickness at least 0.2 pt.

Bleed / trap • 2 mm for labels, stickers etc.
3 mm for brochures, flyers etc.
5 mm for banners, posters, packaging, potcovers etc.

Colour • **CMYK**. When using PMS, clearly state the **PMS number** in the assignment.
Tip. For large black surfaces choose **black: C60% M30% Y20% K100%**.

Please note! • No **extra** whitespace around the CPDF (Layout in clean format)
• In case of printing the backside 100% black. Please note **no** CMYK structure
• Always leave space for the product code. Font size of the product code must be **at least 9 points!**

Open File

Package • Create a package in InDesign and Illustrator from the open file so that all links and fonts are delivered as well.

Fonts • Please note: Fonts that are used in graphics must be delivered as well.
These fonts are not included when making a Package from InDesign.

Images • Always deliver images in 300 DPI and CMYK colour structure.

Supply options

WeTransfer • direct via upload to the relevant contact person.

Mail • Please note that when delivering fonts, kindly send them as a zip file.

Questions • We are happy to help! **T +31 (0)75 64 76 767** • **E info@floramedia.com**

In addition to the supplied files, please provide a list of your products in a Word and/or Excel-file.